



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

All n & Gledhill

COPY OF PAPERS
ORIGINALLY FILED

Patent Application No. 10/083,832

Filing Date: 02/27/02

For: **Method and Apparatus for Cleaning
Inkjet Cartridges**

Attorney Docket No. 4795-005

Cary, North Carolina
May 22, 2002

Director of Patents
Washington, D.C. 20231

TRANSMITTAL OF PRIORITY DOCUMENT

Sir:


Enclosed for filing in connection with the above-referenced matter is a certified true copy of Singapore Application No. 200105516-9.

Respectfully submitted,
Coats & Bennett, P.L.L.C.

By:

Larry L. Coats
Registration No. 26,620

Telephone: (919) 854-1844
Fax: (919) 854-2084



286 #3
6-17-02

RECEIVED

JUN - 5 2002

TECHNOLOGY CENTER 2900



**REGISTRY OF PATENTS
SINGAPORE**

This is to certify that the annexed is a true copy of the following
Singapore patent application as filed in this Registry.

Date of Filing : 10 SEPTEMBER 2001

Application Number : 200105516-9


Applicant(s) : DATA STORAGE INSTITUTE

Title of Invention : METHOD AND APPARATUS FOR
CLEANING INKJET CARTRIDGES

TECHNOLOGY CENTER 2800

JUN -5 2002

RECEIVED



Sharmaine Wu Shee Mei
Assistant Registrar
for REGISTRAR OF PATENTS
SINGAPORE

PATENTS FORM 1**SINGAPORE
PATENTS ACT
(CHAPTER 221)
PATENTS RULES**

Rule 19


The Registrar of Patents
Registry of Patents10 SEP 2001
200105516-9**REQUEST FOR THE GRANT OF A PATENT**THE GRANT OF A PATENT IS REQUESTED BY THE UNDERSIGNED ON THE BASIS OF
THE PRESENT APPLICATION

I. Title of Invention	METHOD AND APPARATUS FOR CLEANING INKJET CARTRIDGES	
II. Applicant(s) (See note 2)	(a) Name	DATA STORAGE INSTITUTE
	Body Description/ Residency	A company limited by guarantee
	Street Name & Number	DSI Building, 5 Engineering Drive 1 (off Kent Ridge Crescent, NUS)
	City	
	State	
	Country	Singapore 117608
	(b) Name	
	Body Description/ Residency	
	Street Name & Number	
	City	
	State	
	Country	
	(c) Name	
	Body Description/ Residency	
	Street Name & Number	
	City	
	State	
	Country	

10 SEP 2001
200105516-9

III. Declaration of Priority <i>(see note 3)</i>	Country/Country Designated		File No.	
	Filing Date			
	Country/Country Designated		File No.	
	Filing Date			
	Country/Country Designated		File No.	
	Filing Date			
IV. Inventors <i>(see note 4)</i> (a) the applicant(s) is/are the sole/joint inventor(s) (b) A statement on Patents Form 8 is/will be furnished.	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> No		
V. Name of Agent (if any) <i>(See note 5)</i>	ALLEN & GLEDHILL			
VI. Address for Service <i>(See note 6)</i>	Block/Hse No.	36	Level No.	18
	Unit No./PO Box	01	Postal Code	068877
	Street Name	ROBINSON ROAD		
	Building Name	CITY HOUSE		
VII. Claiming an earlier filing date under Section 20(3), 26(6) or 47(4). <i>(See note 7)</i>	Application No.			
	Filing Date			
	[Please tick in the relevant space provided]: () Proceeding under rule 27(1)(a). Date on which the earlier application was amended = or _____ () Proceeding under rule 27(1)(b).			

10 SEP 2001
200105516-9

<p>VIII. Invention has been displayed at an International Exhibition (See note 8)</p>	<div style="display: flex; justify-content: space-around; align-items: center;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </div>																	
<p>IX. Section 114 requirements (See note 9)</p>	<p>The invention relates to and/or used a micro-organism deposited for the purposes of disclosure in accordance with Section 114 with a depository authority under the Budapest Treaty</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No </div>																	
<p>X. Check List (To be filled in by applicant or agent)</p>	<p>A. The application contains the following number of sheet(s):-</p>																	
	<table border="1"> <tr><td>1. Request</td><td>4</td><td>Sheets</td></tr> <tr><td>2. Description</td><td>12</td><td>Sheets</td></tr> <tr><td>3. Claim(s)</td><td>3</td><td>Sheets</td></tr> <tr><td>4. Drawing(s)</td><td>7</td><td>Sheets</td></tr> <tr><td>5. Abstract</td><td>1</td><td>Sheets</td></tr> </table>	1. Request	4	Sheets	2. Description	12	Sheets	3. Claim(s)	3	Sheets	4. Drawing(s)	7	Sheets	5. Abstract	1	Sheets		
	1. Request	4	Sheets															
	2. Description	12	Sheets															
3. Claim(s)	3	Sheets																
4. Drawing(s)	7	Sheets																
5. Abstract	1	Sheets																
<p>B. The application as filed is accompanied by:-</p>																		
<table border="1"> <tr><td>1. Priority document</td><td></td></tr> <tr><td>2. Translation of priority document</td><td></td></tr> <tr><td>3. Statement of Inventorship & right to grant</td><td>X</td></tr> <tr><td>4. International Exhibition certificate</td><td></td></tr> </table>	1. Priority document		2. Translation of priority document		3. Statement of Inventorship & right to grant	X	4. International Exhibition certificate											
1. Priority document																		
2. Translation of priority document																		
3. Statement of Inventorship & right to grant	X																	
4. International Exhibition certificate																		
<p>XI. Signature(s) (See note 10)</p>	<p>Applicant (a)</p>																	
	<p>Date</p>	<p>10 September 2001</p>																
	<p>Applicant (b)</p>																	
	<p>Date</p>																	
	<p>Applicant (c)</p>																	
	<p>Date</p>																	

200105516-9
10 SEP 2001

NOTES:

1. This form when completed, should be brought or sent to the Registry of Patents together with the prescribed fee and 3 copies of the description of the invention, and of any drawings.
2. Enter the name and address of each applicant in the spaces provided at paragraph II. Names of individuals should be indicated in full and the surname or family name should be underlined. The names of all partners in a firm must be given in full. The place of residence of each individual should also be furnished in the space provided. Bodies corporate should be designated by their corporate name and country of incorporation and, where appropriate, the state of incorporation within that country should be entered where provided. Where more than 3 applicants are to be named, the names and address of the fourth and any further applicants should be given on a separate sheet attached to this form together with the signature of each of these further applicants.
3. The declaration of priority at paragraph III should state the date of the previous filing, the country in which it was made, and indicate the file number, if available. Where the application relied upon in an International Application or a regional patent application e.g. European patent application, one of the countries designated in that application [being one falling under the Patents (Convention Countries) Order] should be identified and the name of that country should be entered in the space provided.
4. Where the applicant or applicants is/are the sole inventor or the joint inventors, paragraph IV should be completed by marking the "YES" Box in the declaration (a) and the "NO" Box in the alternative statement (b). Where this is not the case, the "NO" Box in declaration (a) should be marked and a statement will be required to be filed on Patents Form 8.
5. If the applicant has appointed an agent to act on his behalf, the agent's name should be indicated in the spaces available at paragraph V.
6. An address for service in Singapore to which all documents may be sent must be stated at paragraph VI. It is recommended that a telephone number be provided if an agent is not appointed.
7. When an application is made by virtue of section 20(3), 26(6) or 47(4), the appropriate section should be identified at paragraph VII and the number of the earlier application or any patent granted thereon identified. Applicants proceeding under section 26(6) should identify which provision in rule 27 they are proceeding under. If the applicants are proceeding under rule 27(1)(a), they should also indicate the date on which the earlier application was amended.
8. Where the applicant wishes an earlier disclosure of the invention by him at an International Exhibition to be disregarded in accordance with section 14(4)(c), then the "YES" Box at paragraph VIII should be marked. Otherwise the "NO" Box should be marked.
9. Where in disclosing the invention the application refers to one or more micro-organisms deposited with a depository authority under the Budapest Treaty, then the "YES" Box at paragraph IX should be marked. Otherwise, the "NO" Box should be marked.
10. Attention is drawn to rules 90 and 105 of the Patent Rules. Where there are more than 3 applicants, see also Note 2 above.
11. Applicants resident in Singapore are reminded that if the Registry of Patents considers that an application contains information the publication of which might be prejudicial to the defence of Singapore or the safety of the public, it may prohibit or restrict its publication or communication. Any person resident in Singapore and wishing to apply for patent protection in other countries must first obtain permission from the Singapore Registry of Patents unless they have already applied for a patent for the same invention in Singapore. In the latter case, no application should be made overseas until at least 2 months after the application has been filed in Singapore.

For Official Use

Application Filing Date : / /
Request received on : / /
Fee received on : / /
Amount : /

* Cash/Cheque/Money Order No :

* Delete whichever is inapplicable.

METHOD AND APPARATUS FOR CLEANING INKJET CARTRIDGES

5 The invention relates to a method and apparatus for cleaning inkjet cartridges in particular using pulsed laser irradiation.

10 It is a conventional technique in manufacturing inkjet cartridges to drill tiny inkjet nozzles (for example, diameter around 40 μm for 2400 dpi inkjet printers) on the polyimide-based flexible circuit by ultra-violet (UV) laser ablation. During the laser drilling, polyimide debris generated will be distributed between the top transparent layer and polyimide substrate. It results in the deposition of black contamination materials around and inside the tiny inkjet nozzles. The contamination affects printing quality subsequently due to improper ink accuracy and poor flexible circuit contact with other device components. Accordingly an important issue in
15 manufacturing the cartridges is to enhance the printer performance by removing surface contamination before the cartridge assembly. As printer technology develops, the tiny inkjet nozzles become smaller and smaller. This makes the contamination removal even more critical. There are two available methods to remove the contamination: chemical solution cleaning, and plasma etching.
20

In the case of chemical solution cleaning, the flexible circuit is put into an appropriate cleaning chemical solution for a certain period of time until the contamination is completely etched away. The flexible circuit is then rinsed by de-ionized (DI) water and dried in a subsequence process.

25 This gives rise to certain problems. High cost and subsequent drying of the flexible circuit are the main drawbacks of this technology. When the chemical solutions etch away the contamination, a chemical reaction with the

polyimide substrate materials can also take place, damaging the substrate. The chemical solution can also be corrosive to the thin conductive circuit on the polyimide substrate. Meanwhile, the flexible circuit has to be dried in the subsequent process after the cleaning, which increases the production cost and processing time, introducing a lower yield. Furthermore, maintenance and disposal of the chemical solutions increase the manufacturing cost as a result of environment protection overheads.

In the plasma etching approach, the flexible circuit is put inside a vacuum chamber and then irradiated by a plasma generated from a plasma source. Surface contamination is then removed due to the plasma interaction with the contamination materials. Contamination debris generated during the plasma etching can be taken away by a gas stream or with a sucker system. This technique also has several problems. The processing needs sophisticated equipment to provide a stable plasma source. In addition, it must be carried out in a vacuum, which increases the cost and manufacturing time. Plasma can etch away not only the contamination but also the polyimide substrate. Furthermore, the thin conductive circuit may be damaged inside the plasma atmosphere.

Though the two methods mentioned above have cleaning effects on the surface contamination, the associated disadvantages significantly affect the productivity of the contamination removal and the reliability of the flexible circuit in manufacturing and increase environment protection overheads.

It is an object of the invention to overcome or mitigate at least some of the above problems. According to the invention there is provided an inkjet circuit cleaning apparatus comprising a circuit holder, a laser for generating a laser beam and an optics subsystem arranged to focus the laser beam onto a circuit surface at the circuit holder.

The optics subsystem preferably includes a beam splitter for splitting off a portion of the beam to regulate the laser beam power. The optics subsystem preferably includes a lens system made of two cylinder lenses for changing a circular laser beam into a narrow and long laser beam, which
5 adjusts the laser beam size, shape and fluence on the flexible circuit.

The optics subsystem preferably includes a galvanometer arranged to scan the laser beam across a circuit surface.

The apparatus preferably further includes a diagnostic subsystem comprising a sensor arranged to sense whether the circuit surface has been
10 cleaned, and preferably the sensor comprises one or more of an acoustic sensor, a plasma signal sensor or a surface pattern inspection monitor. The apparatus preferably further includes an apparatus controller arranged to receive a signal from the sensor and control the cleaning operation accordingly.

15 The laser preferably has a pulse duration of nanoseconds and a wavelength selected from the visible to the infrared range. For example the laser may be a YAG laser with a wavelength 1064nm or 532nm.

The laser beam more preferably has as at least one of the following characteristics: pulse duration 7 nano-seconds; wavelength 532 nm; fluence
20 of 50 mJ/cm²; pulse number of 10.

Preferably the circuit holder is arranged to replace a cleaned circuit by a contaminated circuit.

The apparatus preferably further includes a contaminant removal mechanism, and preferably the contaminant removal mechanism comprises
25 one of a vacuum source or a gas stream source, and the apparatus preferably further comprises a transparent protective cover between the circuit holder and the optics system to trap escaped contaminant.

Preferably the circuit comprises a flexible circuit for an inkjet printer cartridge. According to the invention there is further provided a method of cleaning an inkjet circuit comprising the steps of retaining a circuit to be cleaned in a circuit holder, generating a laser beam from a laser, and
5 focusing and scanning the laser beam on the circuit surface via an optics subsystem.

The method preferably further comprises the steps of detecting when a portion of the circuit surface is cleaned and controlling the galvanometer to scan the beam across a non-cleaned portion of the surface.

10 The method preferably further comprises the step of detecting when a circuit is fully cleaned, and controlling the circuit holder to replace the circuit with a non-cleaned circuit.

The method is preferably for cleaning a flexible circuit of an inkjet printer cartridge.

15 As a result a dry process is available, in air, which does not need the sophisticated equipment and subsequent rinsing and drying process. There are also no chemical solutions involved. By proper control of the processing parameters, the laser irradiation can remove the contamination completely without any damage on the polyimide substrate and the thin conductive
20 circuit. This invention can accordingly offer high productivity and low cost.

In the preferred embodiment appropriate processing parameters such as light wavelength, laser pulse duration, laser fluence and pulse number are selected for removal of the contamination. The contamination area on the polyimide substrate is selectively irradiated by the pulsed laser with the
25 proper processing parameters. When the laser energy is absorbed, its photon energy can easily break the loose chemical bonds of the contamination. It induces a photo-ablation effect with the weak and localised plasma

generation. At the same time, the fast momentum transferring from the laser beam to the polyimide substrate induces the rapid vibration of the substrate surface. It results in the contamination debris ejecting out of the irradiated surface at a high speed. With a gas stream or sucker system, the contamination debris can be easily taken away. In this process, laser fluence can be a critical parameter. With the applied suitable laser fluence, the laser irradiation can remove the contamination completely without any damage on the polyimide substrate. Furthermore, the laser irradiation is limited to around the tiny inkjet nozzle area. There is no laser interaction with the thin conductive circuit.

Therefore, the chemical solution cleaning and plasma etching methods can be replaced by this technology. By using a suitable laser source and proper design of the laser processing parameters, it can achieve the goal of complete removal of the contamination without causing any damage on the polyimide substrate and the thin conductive circuit. Since it is a dry process, the disadvantages of high cost, low yield and chemical disposal can also be avoided.

An embodiment of the invention will now be described, by way of example, with reference to the drawings, of which:

Fig. 1 is an image of a flexible circuit showing contamination;

Fig. 2 is a magnified image of the contamination area of Fig. 1;

Fig. 3A is a schematic diagram of a cleaning apparatus according to the present invention;

Fig. 3B is a perspective view of the lens system of the invention;

Fig. 4 is a schematic diagram of a control system of the present invention;

Fig. 5 is an image demonstrating the cleaning effect according to the

present invention; and

Fig. 6 is a magnified image showing the cleaning effects of the present invention.

Fig. 1 shows an image of a flexible circuit with surface contamination on the polyimide substrate before the laser irradiation. In this picture, the dark lines (1,2) the contamination area. There is a large number of tiny inkjet nozzles in this area, as can be seen from Fig. 2 which shows a magnified image of the surface contamination area on the flexible circuit. In this picture, it can be observed that the dark contamination (3) is distributed around and inside the tiny inkjet nozzles (4).

Fig. 3A shows a schematic diagram of a laser irradiation system according to the present invention arranged to remove the surface contamination on the flexible circuit for inkjet printer cartridge. A pulsed laser (10) (for example, a Nd:YAG laser with pulse duration of 7 ns and wavelength of 1064 nm or 532 nm) provides a pulse energy output for removing contamination on the flexible circuit for inkjet printer cartridge. The laser beam (11) emitted by the laser source (10) passes through a beam sampler (12) which can be a partially silvered mirror with, say 95% transmissivity and 5% reflectivity.

A small amount of the laser energy (5%) is therefore reflected onto an energy meter (14) such that the laser pulse energy is monitored in real-time. This value is sent to a process controller (24) to compare with a pre-set value. If there is some difference between the measured and pre-set values, the process controller (24) will generate a signal to the laser controller (part of laser (10)), which modifies the laser output (11). As a result closed loop control is achieved.

The remainder (95%) of the laser energy is transmitted by sampler

(12) and passes through a lens system (16) including two cylinder lenses, which adjusts the laser beam size, shape and fluence on the flexible circuit (34). The lens system is shown in more detail in Fig.3B. A first, plano-concave lens (36) and second plano-convex lens (38) transform the incoming circular beam (35) into a beam (39) having an elongate elliptical cross section, and adjustment of the lens positions and the focal lengths will further adjust the laser beam size, shape and fluence on the flexible circuit allowing control of the laser fluence in particular within the region from the cleaning threshold (i.e. the fluence threshold at which ablation begins to take place) to the substrate damage threshold (i.e. the upper laser fluence limit). As a result the system can be adjusted to ensure contamination removal without substrate damage. As discussed in more detail below, the laser beam, irradiating the flexible circuit (34) thus has a decontaminating effect.

The surface contamination on flexible circuit (34) has a thickness of about 10 μm . With the proper control of processing parameters (in the preferred embodiment a laser fluence of $50\text{mJ}/\text{cm}^2$ and pulse number of 10 for the above mentioned Nd:YAG laser are found to achieve good results), the contamination can be easily removed without any surface damage to the circuit (34).

The laser pulse is scanned across the circuit (34) by a scanner such as a galvanometer (18). The type of galvanometer is well known and is not shown in detail here, but in brief summary the galvanometer includes a pair of mirrors and corresponding motor drives, one mirror being movable along the Y axis and the other along the X axis allowing fast scanning of the laser beam in two dimensions. Controlled by the process controller (24), this galvanometer (18) changes the laser irradiation position on the sample

surface (32) to remove the contamination at different positions. The galvanometer (18) can be any appropriate reflective or transmissive element, for example moved under mechanical or piezo-electric control. After the laser irradiation of one flexible circuit, the process controller (24) sends a
 5 signal to a sample roller (30) which transports the next contaminated sample (32) to the irradiated position.

To ensure laser irradiation with high quality and effectiveness a signal diagnostics and real-time monitoring system is utilised so that the process can be controlled for removing contamination completely without surface
 10 damage. A suitable sensor (20) which is preferably a microphone to record acoustic waves and/or a photodiode to detect the plasma signal is selected to capture the relevant signal generated during the laser irradiation.

The generation of acoustic waves during laser interaction with materials is well known and is discussed in, for example, "Audible acoustic wave emission in excimer laser interaction with materials", Y.F. Lu et al, J.
 15 Appl. Phys.79(5), 1 March 1996 which also describes an appropriate apparatus for monitoring the acoustic waves produced and is incorporated therein by reference. In particular the principal source of audible acoustic waves is known to be laser ablation and it is found that acoustic wave
 20 emission disappears when a surface is completely clean.

Similarly, it is known from "laser plasma interaction at an early stage of laser ablation" Y.F. Lu et al, J. Appl.Phys. Vol. 85, No. 5 1 March 1999 that, dependent on laser fluence, a photodiode detector voltage following a laser pulse in laser ablation displays a double peak profile in the time
 25 domain. The amplitude of the peak attributable to laser ablation is dependent on the concentrations of ablated materials during the laser ablation and hence the corresponding peak voltage can be monitored to detect any drops in

amplitude which will correspond to the cleaning of the surface.

Alternatively a surface pattern inspection monitor (22) including a CCD camera ensures the cleaning quality in the processing. Either sensors or CCD cameras provide information as to whether the contamination is
5 completely removed. In addition it can be established by the same means whether there is any damage in the flexible circuit after the laser irradiation.

As discussed above, plasma is generated when the laser irradiates contaminants on the circuit and when the contaminants have been removed there will be no plasma generation and hence no acoustic wave or plasma
10 signal such that the microphone/photodiode is simply set to indicate when the detected signal falls below a predetermined threshold. The CCD camera can be used either independently or for the purposes of confirming—simply by detecting contaminants by colour checking for black matter for example - whether there is cleanliness. In addition to this, if the substrate is damaged
15 by the laser irradiation, a further steady acoustic wave/plasma signal is created with a pulse number increase which is detected by the microphone or photodiode allowing an additional check for damage of the substrate.

Fig. 4 shows the signal diagnostics and real-time monitoring system for the laser irradiation of the contamination on the flexible circuit. Sensor
20 (20) preferably comprises a wide-band microphone or photodiode, used to detect the acoustic wave or plasma signal generated during the laser irradiation. It is found that the signal includes characteristic portions which disappear after the contamination complete removal. In this system, the captured signal from the system (40) is sensed at step (42), digitised at step
25 (44) by an A/D converter and then its characteristic value (for example, peak amplitude or intensity) is compared with the database setting at step (46) so as to judge whether the laser irradiation is completed. This is achieved by

signal recognition and comparison to identify the pre-determined characteristic portions according to any appropriate known system. If the contamination is completely removed at step (48), the laser processing will be changed to the next sample. Otherwise at step (50), a further laser pulse regime will be applied for the further irradiation and the steps repeated until the surface contamination is completely removed.

In the alternative system, or a complimentary system, where a surface pattern inspection monitor (22) is used, known image recognition techniques are applied.

Returning to Fig. 3A, during the laser irradiation, the surface contamination becomes debris ejected out of the irradiation area. However, the contamination debris may re-deposit on the sample (32) surface and re-contaminate the flexible circuit (34). Therefore, it is very important to take away the contamination debris before it returns to the flexible circuit during the laser processing. Accordingly a gas stream or sucker system (28) comprising, for example, a gas stream or vacuum source is included in this invention. With the proper control of gas or vacuum nozzle position and size and gas or vacuum flow rate, the contamination debris can be easily transported or sucked away.

In the system setup, the flexible circuit (34) is face down and irradiated by the pulsed laser (10). With this design, the flexible circuit re-contamination by the contamination debris is yet further lessened simply due to gravitational attraction on the debris. However, a small proportion of the debris may escape the gas stream and drop onto the optics, affecting the processing performance. Accordingly, a protective glass surface (26) is included between the flexible circuit (34) and the optics system. With this design, the small amount of debris can be scrubbed away by the operator

after a certain period of the manufacturing time.

Figs. 5 and 6 demonstrate the effectiveness of the laser irradiation system to remove the surface contamination on the flexible circuit (34).

Fig. 5 shows a microscopic photograph of the flexible circuit surface with (line 60) and without (line 62) the laser irradiation. It can be observed from line (60) that the dark line contamination is completely removed after the laser irradiation. Fig. 6 shows a magnified photograph of the flexible circuit surface with region (64) and without region (66) the laser irradiation. It can be observed that the contamination around and inside the tiny inkjet nozzles is completely removed after the laser irradiation. A clean substrate surface without any damage can be observed on the flexible circuit.

It will be appreciated that any appropriate type of laser can be used and any particular power, wavelength, duration and pulse number is only one preferred possibility. Similarly a range of types of inkjet circuit substrate and contaminants can be accommodated according to the invention.

EXPLANATION OF SYMBOLS

	1	Contamination area
	2	Contamination area
5	3	Dark contamination zone
	4	Inkjet nozzles
	10	Laser source
	11	Laser beam
	12	Laser beam sampler
10	14	Laser energy meter
	16	Lens system
	18	Galvanometer
	20	Signal diagnostics & real-time monitoring system
	22	CCD camera
15	24	Process controller
	26	Protection glass
	28	Gas stream or sucker system
	30	Sample roller
	32	Sample for ablation
20	34	Flexible circuit
	35	Incoming circular beam
	36	Cylinder plano-concave lens
	38	Cylinder plano-convex lens
	39	Elongated laser beam
25	40	Laser irradiation system
	42	Signal detection step
	44	A/D converter
	46	Data processor and comparator
	48	"Contamination removed" step
30	50	"Contamination remains" step
	60	Irradiated line
	62	Non-irradiated line
	64	Irradiated region
35	66	Non-irradiated region

CLAIMS

1. An inkjet circuit cleaning apparatus comprising a circuit holder, a laser for generating a laser beam, and an optics subsystem arranged to focus and scan the laser beam onto a circuit surface at the circuit holder.

2. An apparatus as claimed in claim 1 in which the optics subsystem includes a beam splitter for splitting off a portion of the beam to regulate the laser beam power.

10

3. An apparatus as claimed in claim 1 or claim 2 in which the optics subsystem includes a scanner arranged to scan the laser beam across a circuit surface.

4. An apparatus as claimed in any preceding claim in which the optics subsystem includes a lens system for adjusting laser beam size, shape and incident fluence.

5. An apparatus as claimed in any preceding claim further including a diagnostic subsystem comprising a sensor arranged to sense whether the circuit surface has been cleaned.

20

6. An apparatus as claimed in claim 5 in which the sensor comprises one or more of an acoustic sensor, a plasma signal sensor or a surface pattern inspection monitor.

25

7. An apparatus as claimed in claim 5 or claim 6 further including an

apparatus controller arranged to receive a signal from the sensor and control the cleaning operation accordingly.

5 8. An apparatus as claimed in any preceding claims in which the laser has a pulse duration of nanoseconds scale and a wavelength selected from the visible to the infrared range.

10 9. An apparatus as claimed in any preceding claim in which the circuit holder is arranged to replace a cleaned circuit by a contaminated circuit.

10. An apparatus as claimed in any preceding claim further including a contaminant removal mechanism.

15 11. An apparatus as claimed in claim 10 in which the contaminant removal mechanism comprises one of a vacuum source or a gas stream source.

20 12. An apparatus as claimed in claim 10 or 11 further comprising a transparent protective cover between the circuit holder and the optics system to trap escaped contaminant.

13. An apparatus as claimed in any preceding claim in which the inkjet circuit comprises a flexible circuit for an inkjet printer cartridge.

25 14. A method of cleaning an inkjet circuit comprising the steps of retaining a circuit to be cleaned in a circuit holder, generating a laser beam from a laser, and focusing and scanning the laser beam on the circuit

surface via an optics subsystem.

15. A method as claimed in claim 14 further comprising the steps of detecting when a portion of the circuit surface is cleaned and controlling the galvanometer to scan the beam across a non-cleaned portion of the surface.

16. A method as claimed in claim 14 or claim 15 further comprising the step of detecting when a circuit is fully cleaned, and controlling the circuit holder to replace the circuit with a non-cleaned circuit.

17. A method as claimed in any of claims 14 to 16 for cleaning a flexible circuit of an inkjet printer cartridge.

ABSTRACT**METHOD AND APPARATUS FOR CLEANING INKJET
CARTRIDGES**

5

This invention relates to a method and apparatus for removing surface contamination on a flexible circuit 34 for an inkjet printer cartridge by pulsed laser irradiation in air. The contamination 3 around and inside the tiny inkjet nozzles 4 can be completely removed without any damage on the flexible circuit 34 by the laser irradiation. The cleaning mechanisms are laser-induced ablation of the contamination and fast momentum transferring from the laser beam to the contamination materials. Compared with chemical solution cleaning and plasma etching, this technique has high throughput and does not cause flexible circuit damage, due to the fact that there are no water and chemical solutions involved in the process. Meanwhile, the laser irradiation is only limited in a small area around the tiny inkjet nozzles 4. There is no laser interaction with the thin conductive circuit 34.

20 **Fig. 3**




Fig. 1




Fig. 2




Fig. 3A




Fig. 3B




Fig. 4




Fig. 5




Fig. 6